

## Product Specifications



### Main Unit

#### System Type

Monochrome Digital Multifunction Imaging System

#### Functions

Standard: Copy, Print (UFR II), Scan, Send, Store  
 Optional: Print (PCL 5e/6, Adobe® PostScript® 3™), Fax (Up to 4 Lines)

#### Operation Panel

Standard: 8.4" SVGA Full-Color, TFT Screen  
 Optional: 10.4" SVGA Full-Color, TFT Upright Screen

#### Memory

Standard: 1.5GB RAM  
 Maximum: 2GB RAM

#### Hard Disk Drive

Standard: 160GB  
 Maximum: 1TB

#### Mirroring Hard Disk Drive

Optional (160GB, 1TB), Method: RAID1

#### Network Interface Connection

Standard: 10Base-T/100Base-TX/1000Base-T  
 Optional: Wireless LAN (IEEE 802.1x via third-party adapter)

#### Other Interface

Standard: USB 2.0 (Host) x2, USB 2.0 (Device)  
 Optional: Device Port [USB 2.0 (Host) x2], Serial Interface, Copy Control Interface

#### Copy/Print Speed (BW)

Letter: **6275:** Up to 75 ppm  
**6265:** Up to 65 ppm  
**6255:** Up to 55 ppm  
 Legal/11" x 17": **6275:** Up to 45/37 ppm  
**6265:** Up to 39/32 ppm  
**6255:** Up to 39/32 ppm

#### First-Copy-Out Time (Letter)

**6275:** 3.1 Seconds or Less  
**6265/6255:** 3.3 Seconds or Less

#### Paper Sources (20 lb. Bond)

Standard: Dual 1,500-sheet Paper Drawers, Dual 550-sheet Paper Cassettes, 100-sheet Stack Bypass  
 Optional: 3,500-sheet Paper Deck Unit-A1 or 3,500-sheet Paper Deck Unit-D1  
 Maximum: 7,700 Sheets (w/Paper Deck Unit Option)

#### Output Paper Capacity (20 lb. Bond)

Standard: 250 Sheets (w/Copy Tray)  
 Maximum: 4,000 Sheets (w/Staple Finisher or Booklet Finisher)

#### Acceptable Paper Sizes

Drawers: Letter  
 Cassettes: 11" x 17", Legal, Letter, Letter-R, Executive, Statement-R, Custom Size (5-1/2" x 7-1/8" to 11-3/4" x 19-1/4")  
 Bypass: 11" x 17", Legal, Letter, Letter-R, Executive, Statement-R, Custom Size (4" x 5-7/8" to 11-3/4" x 19-1/4")

#### Acceptable Paper Weights

Drawers/Cassettes: 14 lb. Bond to 80 lb. Cover (52 to 220g/m<sup>2</sup>)  
 Bypass: 14 lb. Bond to 140 lb. Index (52 to 256g/m<sup>2</sup>)

#### Duplexing

Paper Size: Standard Automatic Trayless Duplexing (Up to 11" x 17")  
 Paper Weights: 14 lb. Bond to 80 lb. Cover (52 to 220g/m<sup>2</sup>)

#### Media Support

Thin [14 lb. Bond to 16 lb. Bond (52 to 63g/m<sup>2</sup>)], Plain [17 lb. Bond to 24 lb. Bond (64 to 90g/m<sup>2</sup>)], Heavy 1 [25 lb. Bond to 66 lb. Cover (91 to 180g/m<sup>2</sup>)], Heavy 2 [67 lb. Cover to 80 lb. Cover (181 to 220g/m<sup>2</sup>)], Heavy 3 [82 lb. Cover to 140 lb. Index (221 to 256g/m<sup>2</sup>)], Color, Recycled, Pre-Punched, Transparency, Tracing, Labels, Bond, Letterhead, Tab

#### Warm-up Time

From Power On: 30 Seconds or Less  
 From Sleep Mode: 30 Seconds or Less  
 Quick Startup Mode: 7 Seconds\*

#### Power Requirements/Plug

120-127V AC, 60Hz, 16A/NEMA 5-20P

#### Power Consumption

Maximum: 1.92kW  
 Sleep Mode: 0.9W or Less

#### Dimensions (H x W x D)

Without the Upright Control Panel: 48" x 25-3/8" x 30-3/8" (1220mm x 645mm x 770mm)  
 With the Upright Control Panel (To the right edge of the Upright Control Panel in the right-most position): 49-1/4" x 53-3/8" x 30-3/8" (1252mm x 1481mm x 770mm)

#### Installation Space (W x D)

Without the Upright Control Panel: 53-5/8" x 30-3/8" (1362mm x 770mm)  
 With the Upright Control Panel: 74-7/8" x 30-3/8" (1901mm x 770mm)

#### Weight

Approx. 516 lb. (234kg)\*\*

#### Toner (Estimated Yield @ 6% Coverage)

Black: 56,000 Images

## Main Unit (continued)

### Image Reader Unit

#### Scan Resolution

Up to 600 x 600 dpi

#### Acceptable Originals (Glass)

Sheet, Book, 3-Dimensional Objects [Up to 4.4 lb. (2kg)]

#### Maximum Original Size

Up to 11" x 17"

### Document Feeder

#### Scan Method

Single-Pass Duplexing Automatic Document Feeder

#### Acceptable Originals

Paper Sizes: 11" x 17", Legal, Letter, Letter-R, Statement, Statement-R

Paper Weights:

1-sided scanning:

13 lb. Bond to 80 lb. Cover (50 to 220g/m<sup>2</sup>)

2-sided scanning (Black-and-white original):

13 lb. Bond to 80 lb. Cover (50 to 220g/m<sup>2</sup>)

2-sided scanning (Color original):

17 lb. Bond to 80 lb. Cover (64 to 220g/m<sup>2</sup>)

#### Scan Speed (BW/Color; Letter)

Simplex: Up to 120/85 ipm (300 dpi)  
Up to 120/51 ipm (600 dpi)\*\*\*

Duplex: Up to 200/100 ipm (300 dpi)  
Up to 120/51 ipm (600 dpi)\*\*\*

#### Paper Capacity (20 lb. Bond)

300 Sheets

### Copy Specifications

#### First-Copy-Out Time (Letter)

6275: 3.1 Seconds or Less

6265/6255: 3.3 Seconds or Less

#### Multiple Copies

1 to 9,999

#### Copy Exposure

Automatic or Manual (9 Levels)

#### Magnification

25% - 400% (1% Increments)

#### Preset Reductions

25%, 50%, 64%, 73%, 78%

#### Preset Enlargements

121%, 129%, 200%, 400%

#### Basic Copy Features

Preset R/E Ratios by Area, Finishing, Two-Sided, Exposure Adjustment, Original Type Selection, Interrupt Mode, Sample Set, Setting Confirmation/Cancel, Standard Keys, Reset, Guide Display, Job Duration Display, Reserved Copying

#### Special Copy Features

Two-page Separation, Cover/Sheet Insertion, Booklet, Transparency Interleaving, Shift, Margin, Frame Erase, Image Combination, Different-size Original, Job Build, Job Done Notice, Scan Image Check, Mode Memory, Recall, Negative/Positive Inversion, Image Repeat, Mirror Image, Sharpness, Tab Paper Creation, Form Composition, Secure Watermark, Page Numbering, Copy Set Numbering, Watermark and Date, Job Block Combination, Store in User Inbox, Cascade Copy

### Print Specifications

#### Processor

Canon Dual Custom Processor (Shared)

#### Memory

Standard: 1.5GB RAM

Maximum: 2GB RAM

#### Hard Disk Drive

Standard: 160GB

Maximum: 1TB

#### Engine Resolution

1200 x 1200 dpi

#### PDL Support

Standard: UFR II

Optional: PCL 5e/6, Adobe PS 3

#### Print Driver Supported OS

UFR II, PCL 5e/6, Adobe PS 3:

Windows\* (XP/Windows Vista\*/7), Windows Server (2003/2008/2008 R2/SBS 2011/2012), Windows Terminal Servers (Server 2003/Server 2008/Server 2008 R2/2012), Microsoft\* Clustering Server (Server 2003/Server 2003 R2/Server 2008/Server 2008 R2), Citrix (Presentation Server 4.5, Xen App 5.0/6.0/6.5, Xen Desktop 4.0/5.0/5.5), Macintosh\* (OS X 10.5.8 or later, UFR II and PS 3 only), VMware, SAP (PS and PCL Only)

#### Direct Print Support

Standard: TIFF (BW), JPEG

Optional: PDF, EPS\*\*\*, XPS†

#### Print Features

Suspend Job Timeout, Subset Finishing (PS only), Profile Settings, Secure Print, Watermark, Page Border, Header/Footer, Page Layout, Two-sided Printing, Collating, Booklet Printing, Grouping, Mixed Paper Sizes/Orientations, Offsetting, Printing on Transparencies, Front/Back Covers, Toner Reduction, Poster Printing

### Scan Specifications

Network TWAIN Scan: Standard

Network Scan Utility: Color Network ScanGear

### Universal Send Specifications

#### Sending Method

E-mail, I-Fax, File Server (FTP, SMB, WebDAV), Mail Box, Super G3 Fax (Optional)

#### Color Mode

Auto Color Select (Full Color, Grayscale), Auto Color Select (Color, BW), Full Color, Grayscale, BW

#### Scan Resolution\*\*\*

600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi, 150 x 150 dpi, 100 x 100 dpi

#### Address Book Capacity

Max. 1,800 Destinations (Incl. 200 One-Touch Buttons)

#### Communication Protocol

File: FTP (TCP/IP), SMB (TCP/IP), WebDAV

E-mail/I-Fax: SMTP, POP3, I-Fax (Simple, Full)

#### File Format

Standard: TIFF (BW), JPEG, PDF, PDF (Compact), PDF (Apply Policy), PDF (Optimize for Web), PDF/XPS (OCR), PDF/A-1b, XPS, XPS (Compact), OOXML (.pptx)

Optional: PDF (Trace & Smooth), PDF (Encrypted), PDF/XPS (Digital Signature), PDF (Reader Extensions)

#### I-Fax Data Format

BW: TIFF (MH, MR, MMR)

Color: TIFF (Profile-C)

#### Universal Send Features

Two-sided Original, Different-size Originals, Original Type Selection, Book to Two Pages, Density Adjustment, Sharpness, Document Name, Copy Ratio, Erase Frame, Job Build, Delayed Send, Preview, Finished Stamp, Job Done Notice, File Name, Subject/Message, Reply-to, Sender's Name (TTI), E-mail Priority

### Fax Specifications

Maximum Number of Connection Lines: 4

#### Modem Speed

Super G3: 33.6 Kbps

G3: 14.4 Kbps

Compression Method: MH, MR, MMR, JBIG

#### Resolution

400 x 400 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi

Sending/Recording Size: Statement-R to 11" x 17"

#### Fax Features

Job Forwarding, Different-size Originals, Adjusting Overall Density for Scanning, Sharpness, Copy Ratio, Erase Frame, Job Build, Specifying the Sender's Name (when sending fax), Selecting the Telephone Line (when sending fax), Delayed Send, Preview, Finished Stamp, Job Done Notice, Original Type Selection, Two-sided Original, Book to Two Pages

## Main Unit (continued)

### Store Specifications

#### Mail Box (Number supported)

100 User Inboxes, 1 Memory RX Inbox,  
50 Confidential Fax Inboxes  
20,000 Maximum Pages Stored

#### Advanced Box

Available Approx. 15GB (Standard HDD)  
Disk Space: Approx. 629GB (1TB HDD)  
Communication Protocol: SMB or WebDAV  
Supported Client PC: Windows (Windows 2000/XP/7/Windows Vista)  
Concurrent Connections (Max.): SMB: 32, WebDAV: 12 (Active Sessions)  
Advanced Box Features: Disabling Advanced Box, Storage Filtering, Authentication for Advanced Box Log-in, Search Function, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support

#### Memory Media

Standard: USB Memory  
Optional: SD, SDHC, CompactFlash, Memory Stick, Microdrive

### Security Specifications

#### Standard

Department ID Management, Single Sign-On H, Access Management System (Device and Function Level Log-in), Secure Print, Trusted Platform Module, User Access Control of Advanced Box, Mail Box Password Protection, IPv6, Restricting Features (Restricting the Send Function, Restricting New Addresses on Address Book), SSL Encrypted Communication, SNMPv1/v3, MAC/IP Address Filtering, SMTP Authentication, POP Authentication before SMTP, HDD Erase (Up to 3x), HDD Initialize (Up to 9x), HDD Lock, IPsec, Adobe LiveCycle® Rights Management ES2.5 Integration

#### Optional

Removable HDD, HDD Encryption, HDD Mirroring, Encrypted Secure Print, Encrypted PDF, Document Scan Lock, Secure Watermark, IEEE 2600.1 Common Criteria Certification<sup>††</sup>

### Environmental Information

#### ENERGY STAR® Qualified

#### EU RoHS Compliant

#### Ecomark

#### Blue Angel

#### WEEE Directive

## Optional Accessories

### Paper Supply Options

#### Paper Deck Unit-A1

Paper Capacity: 3,500 Sheets [20 lb. Bond (80g/m<sup>2</sup>)]  
Number of Drawers: 1  
Acceptable Paper Weight: 14 lb. Bond to 80 lb. Cover (52 to 220g/m<sup>2</sup>)  
Acceptable Paper Size: Letter  
Acceptable Paper Type: Thin, Plain, Heavy, Color, Recycled, Bond, Pre-Punched  
Power Source/Max. Power Consumption: From the Main Unit/Approx. 39W  
Dimensions (H x W x D): 22-1/2" x 12-3/4" x 23" (570mm x 323mm x 583mm)  
Weight: Approx. 81.6 lb. (37kg)

#### Paper Deck Unit-D1

Paper Capacity: 3,500 Sheets [20 lb. Bond (80g/m<sup>2</sup>)]  
Number of Drawers: 1  
Acceptable Paper Weight: 14 lb. Bond to 80 lb. Cover (52 to 220g/m<sup>2</sup>)  
Acceptable Paper Size: 11" x 17", Legal, Letter, Letter-R  
Acceptable Paper Type: Thin, Plain, Heavy, Color, Recycled, Bond, Pre-Punched  
Power Source/Max. Power Consumption: From the Main Unit/Approx. 39W  
Dimensions (H x W x D): 22-1/2" x 23-5/8" x 24-1/2" (570mm x 601mm x 621mm)  
Weight: Approx. 125.7 lb. (57kg)

### Output Options

#### Copy Tray-Q1

Total Output Capacity: 250 Sheets [20 lb. Bond (80g/m<sup>2</sup>)]  
Acceptable Paper Weight: 14 lb. Bond to 140 lb. Index (52 to 256g/m<sup>2</sup>)  
Acceptable Paper Size: 11" x 17", Legal, Letter, Letter-R, Executive, Statement-R, Custom Size [4" x 5-7/8" to 11-3/4" x 19-1/4" (100mm x 148mm to 297mm x 487.7mm)]  
Acceptable Paper Type: Thin, Plain, Heavy, Color, Recycled, Pre-Punched, Transparency, Tracing, Labels, Bond, Letterhead, Tab  
Dimensions (H x W x D): 6-7/8" x 16-1/2" x 15" (175mm x 420mm x 382mm)  
Weight: Approx. 2.4 lb. (1.1kg)

#### Booklet Finisher-P1

Number of Trays: 3  
Total Output Capacity: 4,000 Sheets (Letter)  
Tray A: 250 Sheets (Letter, Statement-R, Executive) 125 Sheets (11" x 17", Legal, Letter-R)  
Tray B: 1,300 Sheets (Letter, Statement-R, Executive) 650 Sheets (11" x 17", Legal, Letter-R)  
Tray C: 2,450 Sheets (Letter) 1,700 Sheets (Statement-R, Executive) 650 Sheets (11" x 17", Legal, Letter-R)  
Acceptable Paper Weight: 14 lb. Bond to 140 lb. Index (52 to 256g/m<sup>2</sup>)  
Acceptable Paper Size: 11" x 17", Legal, Letter, Letter-R, Executive, Statement-R, Custom Size [4" x 5-7/8" to 11-3/4" x 19-1/4" (100mm x 148mm to 297mm x 487.7mm)]

#### Booklet Finisher-P1 (continued)

Acceptable Paper Type: Thin, Plain, Heavy, Color, Recycled, Pre-Punched, Transparency, Tracing, Labels, Bond, Letterhead, Tab, Coated<sup>†††</sup>  
Staple Positions: **Corner/Double Stapling:** 11" x 17", Legal, Letter, Letter-R, Executive  
**Saddle-Stitch:** 11" x 17", Legal, Letter-R  
Maximum Stapling Capacity: **Letter and Executive:** 50 Sheets [20 lb. Bond (80g/m<sup>2</sup>)]  
**11" x 17", Legal, Letter-R:** 30 Sheets [20 lb. Bond (80g/m<sup>2</sup>)]  
Paper Capacity of Staple Mode: **Tray B and Tray C:** 1,300 Sheets/100 Sets (Letter, Executive), 650 Sheets/50 Sets (11" x 17", Legal, Letter-R)  
Maximum Saddle-Stitch Capacity: 16 Sheets [20 lb. Bond (80g/m<sup>2</sup>)] [including 1 Cover Sheet, up to 140 lb. Index (256g/m<sup>2</sup>)]  
Paper Capacity of Saddle-Stitch Mode: 1 to 5 Sheets/25 sets, 6 to 10 Sheets/15 sets  
Type of Staple: Staple-J1 (5,000 x 3)  
Staple: Staple Cartridge-D2 (2,000 x 3)  
Saddle Fold: 1 Sheet [16 lb. Bond to 140 lb. Index (60 to 256g/m<sup>2</sup>)]  
Power Source/Max. Power Consumption: From the Main Unit/Approx. 155W (including the External 2/3 Hole Puncher-A1) Approx. 143W (excluding the External 2/3 Hole Puncher-A1)  
Dimensions (H x W x D): 44-1/8" x 25-1/2" (30"\*\*\*\*) x 25-7/8" [1121mm x 646mm (761 mm\*\*\*\*) x 656 mm]  
Weight: 159 lb. (72kg)  
**Staple Finisher-P1**  
Number of Trays: 3  
Total Output Capacity: 4,000 Sheets (Letter)  
Tray A: 250 Sheets (Letter, Statement-R, Executive) 125 Sheets (11" x 17", Legal, Letter-R)  
Tray B: 1,300 Sheets (Letter, Statement-R, Executive) 650 Sheets (11" x 17", Legal, Letter-R)  
Tray C: 2,450 Sheets (Letter) 1,700 Sheets (Statement-R, Executive) 650 Sheets (11" x 17", Legal, Letter-R)  
Acceptable Paper Weight: 14 lb. Bond to 140 lb. Index (52 to 256g/m<sup>2</sup>)  
Acceptable Paper Size: 11" x 17", Legal, Letter, Letter-R, Executive, Statement-R, Custom Size [4" x 5-7/8" to 11-3/4" x 19-1/4" (100mm x 148mm to 297mm x 487.7mm)]  
Acceptable Paper Type: Thin, Plain, Heavy, Color, Recycled, Pre-Punched, Transparency, Tracing, Labels, Bond, Letterhead, Tab, Coated<sup>†††</sup>  
Staple Positions: **Corner/Double Stapling:** (11" x 17", Legal, Letter, Letter-R, Executive)  
Maximum Stapling Capacity: **Letter and Executive:** 50 Sheets [20 lb. Bond (80g/m<sup>2</sup>)]  
**11" x 17", Legal and Letter-R:** 30 Sheets [20 lb. Bond (80g/m<sup>2</sup>)]  
Paper Capacity of Staple Mode: **Tray B and Tray C:** 1,300 Sheets/100 Sets (Letter, Executive), 650 Sheets/50 Sets (11" x 17", Legal, Letter-R)  
Type of Staple: Staple-J1 (5,000 x 3)  
Power Source/Max. Power Consumption: From the Main Unit/Approx. 147W (Including the External 2/3 Hole Puncher-A1) Approx. 136W (Excluding the External 2/3 Hole Puncher-A1)  
Dimensions (H x W x D): 44-1/8" x 25-3/8" (30"\*\*\*\*) x 25-7/8" [1121mm x 644mm (761mm\*\*\*\*) x 656mm]  
Weight: 106 lb. (48kg)

## Optional Accessories

### Output Options (continued)

#### External 2/3-Hole Puncher-A1

Acceptable Punch  
Paper Weight: 14 lb. Bond to 140 lb. Index (52 to 256g/m<sup>2</sup>)

Acceptable Punch  
Thin, Plain, Heavy, Color, Recycled, Tab, Bond, Paper Type: Coated<sup>†††</sup>

Acceptable Punch  
Paper Size: 11" x 17", Legal, Letter, Letter-R

Punch Type: 2 Holes: (Legal, Letter-R)  
3 Holes: (11" x 17", Letter)

Distance Between  
2 Holes: 2-3/4" (70mm)  
Punch Holes: 3 Holes: 4-1/4" (108mm)

Punch Waste  
Tray Capacity: Approx. 10,000 Sheets [20 lb. Bond (80g/m<sup>2</sup>)]

Power Source: From the Main Unit  
Dimensions 32-1/2" x 4-1/4" x 24-1/4"  
(H x W x D): (825mm x 107mm x 615mm)  
Weight: Approx. 17 lb. (7.7kg)

#### Document Insertion Unit-L1

Acceptable Media: Covers and Inserts

Number of Trays: 1

Tray Capacity: 100 Sheets [20 lb. Bond (80g/m<sup>2</sup>)]

Acceptable Paper Weight: 16 lb. Bond to 140 lb. Index (60 to 256g/m<sup>2</sup>)

Acceptable Thin, Plain, Heavy, Color, Recycled, Tab, Bond, Paper Type: Letterhead, Coated<sup>†††</sup>

Acceptable Paper Size: 11" x 17", Legal, Letter, Letter-R, Executive

Power Source/  
Max. Power  
Consumption: 100-240V AC, 50/60Hz, 1.0A/Approx. 84W

Dimensions 48-7/8" x 26-1/8" x 26-3/4"  
(H x W x D): (1242mm x 662mm x 679mm)

Weight: Approx. 88.2 lb. (40kg)

#### Document Insertion/Folding Unit-H1

Folding Method: Roller Pressure Folding

Folding Type: Z-Fold, C-Fold

Acceptable Z-Fold: 16 lb. Bond to 28 lb. Bond (60 to 105g/m<sup>2</sup>)  
Paper Weight: C-Fold: 16 lb. Bond to 28 lb. Bond (60 to 105g/m<sup>2</sup>)  
Insertion Unit: 16 lb. Bond to 140 lb. Index (60 to 256g/m<sup>2</sup>)

Acceptable Z-Fold/C-Fold:  
Paper Type: Thin, Plain, Color, Recycled  
Insertion Unit:  
Thin, Plain, Heavy, Color, Recycled, Tab, Bond, Letterhead, Coated<sup>†††</sup>

Acceptable Z-Fold: 11" x 17", Legal, Letter-R  
Paper Size: C-Fold: Letter-R  
Insertion Unit: 11" x 17", Legal, Letter, Letter-R, Executive

#### Document Insertion/Folding Unit-H1 (continued)

Power Source/  
Max. Power  
Consumption: 100-240V AC, 50/60Hz, 1.0A/Approx. 170W  
Dimensions 48-7/8" x 26-1/8" x 26-3/4"  
(H x W x D): (1242mm x 662mm x 679mm)  
Weight: Approx. 168 lb. (76kg)

### Additional Print Controller Options

#### imagePASS-U2 Controller

Type: External  
Processor: Intel® Pentium® Processor E5300 2.60GHz  
System: Fiery® System 10  
PDL Support: Adobe PS 3, PCL 5e/6  
Print Resolution: 1200 x 1200 dpi  
2400 dpi equivalent x 600 dpi  
Memory: 2GB (Standard/Maximum)  
HDD: 250GB

Interfaces (to LAN): 10Base-T/100Base-TX/1000Base-T

Dimensions 12-1/2" x 5-1/2" x 15-1/2"  
(H x W x D): (317.5mm x 139.7mm x 393.7mm)

Utility Software:  
• imagePASS-U2 Driver  
• Command WorkStation® 5  
• Remote Scan 5.3  
• Web Tools

Standard Features:  
• Hot Folder  
• Secure Erase  
• VDP Enhancement

Options:  
• SeeSequence Suite  
• SeeSequence Impose  
• SeeSequence Compose  
• Removable Hard Disk Drive  
• Integration Interface and Stand (19" display, keyboard, mouse, and furniture stand)  
• ImageViewer

- Universal Send Security Feature Set-D1
- Universal Send Digital User Signature Kit-C1
- Super G3 Fax Board-AL1
- Super G3 2nd Line Fax Board-AL1<sup>▲</sup>
- Super G3 3rd/4th Line Fax Board-AL1<sup>▲▲</sup>
- Remote Fax Kit-A1<sup>▲▲▲</sup>
- Secure Watermark-B1
- Silix Wireless Bridge SX-2500CG
- USB Device Port-A2
- Multimedia Reader/Writer-A2<sup>\*</sup>
- Additional Memory Type D (512MB)
- Document Scan Lock Kit-B1
- HDD Data Encryption and Mirroring Kit-C5
- Removable HDD Kit-AG1
- 2.5-inch/160GB HDD-J1
- 2.5-inch/1TB HDD-K1
- Voice Guidance Kit-F2<sup>\*\*</sup>
- Voice Operation Kit-C2<sup>\*\*</sup>
- Remote Operator's Software Kit-B1
- Copy Control Interface Kit-A1<sup>\*\*\*</sup>
- IEEE 2600.1 Common Criteria Certification<sup>††</sup>

\* If "Quick Startup Settings for Main Power" is set to ON, it takes 7 seconds until the key operation on the touch-panel display is available after turning on the main power.

\*\* Including toner bottle and Duplex Color Image Reader.

\*\*\* Standard color scan support is up to 300 dpi. Up to 600 dpi scanning requires Additional Memory Type D (512 MB).

\*\*\*\* EPS can be printed directly only from Remote User Interface.

† XPS cannot be printed directly from the Web Access software.

†† Not available at time of launch.

††† Coated paper can be loaded from the Document Insertion Unit only.

†††† When the Auxiliary Tray is extended.

■ Requires the Copy Card Reader Attachment Kit-A2.

■ Requires PCL Printer Kit-AU1.

■ Requires Additional Memory Type D (512MB).

■ Requires Direct Print Kit-H1 for printing PDF files.

▲ Requires Super G3 Fax Board-AL1.

▲▲ Requires Super G3 2nd Line Fax Board-AL1.

▲▲▲ Cannot be installed with Super G3 Fax Board-AL1.

\* Requires USB Device Port-A2.

\*\* Voice Guidance Kit-F2 and Voice Operation Kit-C2 cannot be installed together.

\*\*\* Cannot be installed with Copy Card Reader-F1.

### Other Optional Accessories

- Upright Control Panel Set-E1
- Utility Tray-A2
- USB Keyboard
- Universal Keyboard Stand-A1
- Copy Card Reader-F1<sup>■</sup>
- Braille Label Kit-F1
- ADF Access Handle-A1
- Convenience Stapler-B1
- PCL Printer Kit-AV1
- PCL International Font Set-A1<sup>■</sup>
- PS Printer Kit-AV1<sup>■</sup>
- Direct Print Kit (for PDF/XPS)-H1<sup>■</sup>
- Encrypted Secure Print Software-D1
- Barcode Printing Kit-D1<sup>■</sup>
- Web Access Software-H1<sup>■</sup>
- Universal Send Advanced Feature Set-F1

**Canon**  
image*ANYWARE*

1-800-OK-CANON  
www.usa.canon.com

Canon U.S.A., Inc.  
One Canon Park  
Melville, NY 11747

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has determined that these products meet the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. CANON, IMAGERUNNER, IMAGEPASS, and the GENUINE logo are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. IMAGEWARE is a registered trademark of Canon U.S.A., Inc. in the United States and is a trademark of Canon Inc. in certain other countries. IMAGEANYWARE is a trademark of Canon. All other referenced product names and marks are trademarks of their respective owners and are hereby acknowledged. Specifications and availability subject to change without notice. Some items may not be available at this time, please check for availability. All printer output images are simulated.

©2013 Canon U.S.A., Inc. All rights reserved.

